

II HIGHLIGHTS

Monocular panoramic camera

- Extensive field of vision 210° degrees of camera coverage, no hidden corners, and highly efficient route planning
- High precision postioning Millimeter-level positioning accuracy
- Multi-task with Ease Registers about 1,000 landmarks simultaneously

Richtech's control platform

- Al computing power
 Three trillion operations per secoond
- Comprehensive vision system

 10 bit color depth with support for over a billion hues
- ARM architecture

 Small size, low temperature output, power

consumption reduced by more than 50%



- High frame rate 45FPS
- Detailed captures
 Recognition accuracy of about two centimeters
- Ultra-responsive
 Response time of about 20 milliseconds
 - Wide visual angle
 135° degrees of vision





- High rotation speed 900 rpm
- © Extreme precision 0.125 degrees
- Long detection distance
 Limit distance of 30 meters





- High-level precision spot size <1 centimeter
- Anti-interference
 Infrared spectrum of 808 nanometer

II PRODUCT SPECS

Basic specs	
Size L * W* H	44 in x 22 in x 45 in
Weight	557 lbs (without water)
Performance specs	
Cleanable width	20 in
Width of suction rake	30 in
Pressure on the ground	60 lbs
Brush pressure per unit area	13.2 g/cm ²
Fresh water tank volume	17 gal
Waste water tank volume	13 gal
Circulating water system	N
Travel speed	2.5 mph
Work efficiency	21,958 sqft/h
Gradeability	6°
Electronic system	
Voltage	DC24V
Battery life	3 - 4h
Battery capacity	DC24V, 120Ah
Intelligent system	
Navigation scheme	Vision + Laser
Sensor solution	Monocular panoramic camera / binocular camera/ lidar/3Dtof camera/ultrasonic wave/IMU/ Electronic bumper
Automobile data recorder	Selectable

PROPRIETARY TECHNOLOGY, SELF-DEVELOPED DESIGN

Proprietary Al algorithm that combines laser and camera vision for location and composition. A variety of key sensors for robot have been developed independently.

SAFE AND RELIABLE IN ANY ENVIRONMENT

Multiple protection systems, intelligent recognition, and rapid response combines together to ensure safety during operation.

EASY TO USE, SMOOTH INTERACTION

We've optimized practical logic and interaction touchpoints to create a polished, zero-cost robot operating system for users.